

# Pure-Fit® SBP Braid-Reinforced Hose



## Pure-Fit® SBP Braid-Reinforced Hose

Pure-Fit® SBP platinum-cured braid-reinforced silicone hose is an ultra-flexible, high-purity hose utilized for higher pressure sanitary transfer applications in the pharmaceutical and biotech industries.

Pure-Fit® SBP hose has an operating temperature range of -80°F (-62°C) to 500°F (260°C).

## Characteristics

The manufacturing process is carefully controlled from receiving through production and inspection and lot traceability is readily accessible and batch numbers are assigned. All packages are identified by external labeling on both the bag and the high-quality, crush-proof box.

## Biocompatibility

Pure-Fit® SBP hose is manufactured from the finest grade of silicone materials and is fully tested to meet USP Class VI criteria.

**Tri-Canada**

905.677.9000 • 1.800.486.7863  
www.tricanada.com

## BIOPHARMACEUTICAL PRODUCTS

### *Platinum-Cured Braid-Reinforced Silicone Hose*

#### Features/Benefits

- Ultra-Flexible
- Improved Bend Radius over Wire-Reinforced Tubing
- Sterilizable
- Autoclavable
- Imparts No Taste or Odor
- Color Striping Available
- Criss-Cross Color Braiding Available
- Available in 50-foot Lengths

#### Typical Applications

- Pharmaceutical Bulk-Product Transfer
- Vessel or tank transfer
- Cell Cultures
- Load Cell

#### Connections

- Radially Crimped 316L SS or Non-Metallic Fittings
- Adaptor Connections

## Pure-Fit® SBP Hose Inventory Sizes

Part Number	ID Inches (mm)	OD Inches (mm)	Wall Inches	Recommended Working Pressure PSI at 68°F	Minimum Burst Pressure, PSI at 68°F	Minimum Bend Radius Inches	Weight Per Foot, Lb.
HOSSBP-04	.250 (6.4)	.500 (13.2)	.125	150	550	1.55	.08
HOSSBP-06	.375 (9.5)	.625 (16.6)	.125	135	480	1.75	.12
HOSSBP-08	.500 (12.7)	.875 (20.3)	.187	125	390	2.00	.16
HOSSBP-10	.625 (15.9)	1.000 (25.4)	.187	120	360	2.50	.22
HOSSBP-12	.750 (19.1)	1.125 (27.9)	.187	90	300	3.00	.26
HOSSBP-16	1.000 (25.4)	1.375 (34.5)	.187	60	220	4.00	.35

NOTE: For every 100°F increase in working temperature, stated burst pressures of SBP Series hose decrease by 10%.

NOTE: Consult factory for availability of other sizes, such as 3/16-inch I.D. (.187-in.).

## Sterilization Methods

- Autoclavable
- Radiation - up to 2.5 Mrad (25 Kilogray)
- Gas - Ethylene Oxide

Distributed By:

**Tri-Canada**

7033 Telford Way #20, Mississauga, ON L5S 1V4  
 Tel: **905.677.9000** • Toll Free: **1.800.486.7863**  
[www.tricanada.com](http://www.tricanada.com)

Pure-Fit® is a registered trademark.

**PURE-FIT® HOSE IS NOT INTENDED FOR USE AS AN IMPLANT MATERIAL**

## BIOPHARMACEUTICAL PRODUCTS

*Come through clean.™*

Saint-Gobain Performance Plastics

460 Milltown Road  
 Bridgewater, NJ 08807  
 Tel: (800) 435-3992  
 Tel: (908) 218-8888  
 Fax: (908) 218-9009



**IMPORTANT:** It is the user's responsibility to ensure the suitability and safety of Saint-Gobain Performance Plastics tubing for all intended uses. Laboratory and clinical tests must be conducted in accordance with applicable regulatory requirements in order to determine the safety and effectiveness for use of tubing in any particular application.

For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product to be free from defects in materials and workmanship. Our only obligation will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risk, if any, including the risk of injury, loss or damage, direct or consequential, arising out of the use, misuse, or inability to use, this product. THIS WARRANTY IS IN LIEU OF THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED. No deviation is authorized.

Saint-Gobain Performance Plastics Corporation assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to those products. All such advice is given and accepted at the buyer's risk.